

### Innovation in Banding

### “The newest generation”



#### ■ FEATURES

With our new DALLIPAK DB-Series we have built a system with sets new standards in the banding industry. A huge amount of different components makes it possible to satisfy our customers needs exactly.

Printed or unprinted material is exactly positioned. Beside the graphical industry, it is also in use in other branches like the food industry or pharma industry.

- Economic banding material
- Safe and stable in use
- Automatic tape feed in
- Photolense eye or foot switch
- Tension from soft to strong
- High speed with up to 40 cycles/min

#### ■ STANDARD FILM - Transparent

Width	Strength	Length
28 mm	50 µm - 100 µm	1500 m
48 mm	50 µm - 100 µm	1500 m
77 mm	50 µm - 100 µm	1500 m
102 mm	50 µm - 100 µm	1500 m

#### ■ STANDARD PAPER (White/Brown)

Width	Strength	Length
28 mm	70 g/m <sup>2</sup> - 90 g/m <sup>2</sup>	800 m
48 mm	70 g/m <sup>2</sup> - 90 g/m <sup>2</sup>	800 m
77 mm	70 g/m <sup>2</sup> - 90 g/m <sup>2</sup>	800 m
102 mm	70 g/m <sup>2</sup> - 90 g/m <sup>2</sup>	800 m

# Description

Future proved banding "Fast - soft to strong"

- Advantages**
- Simple in use
  - Display with production data
  - Operation possible on both sides
  - SPS control
  - Excellent construction

## STANDARD - MACHINE TYPES

Machine type	DB 24	DB 32
Frame width	240 mm	320 mm
Frame height	150 mm	200 mm
Working height	950 mm	950 mm
Width	600 mm	600 mm
Depth	500 mm	500 mm
Weight	70 kg	72 kg
Cycles per minute	36	34

Machine type	DB 40	DB 48
Frame width	400 mm	480 mm
Frame height	250 mm	350 mm
Working height	950 mm	950 mm
Width	760 mm	760 mm
Depth	500 mm	500 mm
Weight	72 kg	72 kg
Cycles per minute	32	30

## OPTIONS

- Special machine types on request
- Printing device
- Product stopper
- Pneumatic press
- Variable height
- Thermotransfer-printer

## TECHNICAL DATA

Tension	Variable
Voltage	230V / 50 Hz
Energy	~ 0,5 kW
Roll length	Up to 1500 meters



DB32 with built on printer

# Banding center DALLIPAK

DALLIPAK GmbH  
Gewerbepark Mitterfeld 1  
2523 Tattendorf - Austria

Tel.: +43 / (0)2253 / 81045  
Fax.: +43 / (0)2253 / 81046  
E-Mail: [info@dallipak.at](mailto:info@dallipak.at)

Internet: <http://www.dallipak.at/>

Changes, printing and other errors reserved.

DALLIPAK DB-Series